



NOTES:

- 1) LEFT TURN LANES 250 FT. STANDARD LEFT TURN POCKETS ON ALL LEGS, REQUIRED.
(150 FT. MINIMUM, BASED ON EXISTING CONDITIONS.
- 2) RIGHT TURN LANES 150 FT. STANDARD TURN LANE ON ALL LEGS, REQUIRED.
(100 FT. MINIMUM, BASED ON EXISTING CONDITIONS AND SITE DEVELOPMENT)
- 3) TRANSITIONS CURB TRANSITIONS FROM NEW WIDENING TO EXISTING ROADWAYS SHALL BE
DETERMINED BASED ON EXISTING ROADWAY WIDTHS AND SITE DEVELOPMENT
(ALL SIDES)
- 4) BUS BAYS MINIMUM 80 FT. REQUIRED ON ALL "FARSIDE" LEGS OF THE INTERSECTION
(MAY BE ADJUSTED TO EXACT LOCATION, BASED ON EXISTING STRUCTURES)
- 5) SIDEWALK WIDTH STANDARD 10' COMMERCIAL SIDEWALK REQUIRED ON ALL LEGS EXCEPT IN
INFILL AREAS. INFILL AREA MINIMUM PATTERN IS 7' SOLID.
- 6) LANDSCAPE EACH SITE MUST BE EVALUATED FOR SURFACE OR POTTED LANDSCAPING IN PUBLIC RIGHT OF WAY
IF LANDSCAPING IS REQUIRED, MUST BE IRRIGATED FROM PUBLIC SERVICE POINT.